

## Indoor Ambience Monitoring Sensor

Featuring LoRaWAN®

### IOT-S500AM11



### ◆ Introduction

IOT-S500AM11 is a compact indoor ambience monitoring sensor for measurement of temperature, humidity, light, CO2 concentration, HCHO/O3 level, TVOC, barometric pressure, PM2.5, PM10 and motion. The data will be shown on the E-ink screen in real-time, which helps to measure the indoor environment and comfort. IOT-S500AM11 is widely used for offices, stores, classrooms, hospitals, etc.

Sensor data is transmitted using LoRaWAN® technology. Combining Linovision LoRaWAN® gateway and Linovision IoT Cloud, users can manage all sensor data remotely and visually.

### ◆ Features

- Integrated with multiple sensors like humidity, temperature, CO2, light, barometric pressure, PM2.5, PM10, etc.
- Multiple display modes and clear emoticon to easily understand the comfort levels via screen
- Support batteries or DC power supply
- Equipped with traffic LED and buzzer to indicate device status and threshold alarms
- Support more than 20,000 data records store locally
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Linovision IoT Cloud

## ◆ Specifications

Model	IOT-S500AM9	IOT-S500AM11
<b>Wireless Transmission</b>		
Technology	LoRaWAN®	
Frequency	CN470/RU864/IN865/EU868/US915/AU915/KR920/AS923	
Tx Power	16dBm(868MHz)/22dBm(915MHz)/19dBm(470MHz)	
Sensitivity	-137dBm @300bps	
Work Mode	IOT-S500AM9: Class A IOT-S500AM11: Class C	
<b>Sensors</b>		
<b>Temperature</b>		
Range	-40°C - 85°C	
Accuracy	± 1°C	
Resolution	0.1°C	
<b>Humidity</b>		
Range	0% - 100% RH	
Accuracy	± 3%	
Resolution	0.5% RH	
<b>PIR</b>		
Detection Area	80 ° Horizontal, 55 ° Vertical	
Detection Range	5 m	
Status	Vacant/Occupied	
<b>Light</b>		
Range	0-60000 Lux (display as 6 levels, 0-5)	
<b>TVOC</b>		
Range	0-500 (IAQ Index)	
Accuracy	±15 %	
<b>Barometric Pressure</b>		
Range	300 - 1100 hPa (-40°C - 85°C)	
Accuracy	±0.6 hPa	
Resolution	0.1 hPa	
<b>Carbon Dioxide (CO<sub>2</sub>)</b>		
Range	400 - 5000 ppm	400 - 2000 ppm

Accuracy	±30 ppm or ±3 % of reading	±50 ppm or ±5 % of reading
Resolution	1 ppm	1 ppm
<b>PM2.5 &amp; PM10</b>		
Range	—	0 - 1000 µg/m <sup>3</sup>
Accuracy	—	0-100(±10µg/m <sup>3</sup> ), 100-1000(±10 %)
Resolution	—	1 µg/m <sup>3</sup>
<b>Formaldehyde (HCHO)</b>		
Range	—	0 - 6 mg/m <sup>3</sup>
Accuracy	—	0 %
Resolution	—	0.01 mg/m <sup>3</sup>
<b>Ozone (O<sub>3</sub>)</b>		
Range	—	0 - 10 ppm
Accuracy	—	±5 % FS
Resolution	—	0.01 ppm
<b>Display &amp; Configuration</b>		
Display	4.2-inch Black & White E-Ink Screen	
Button	1 × External Button + 1 × Reset Button	
LED & Buzzer	1 × Traffic Light Status Indicator + 1 × Buzzer	
Configuration	<ol style="list-style-type: none"> <li>1. Mobile App via NFC</li> <li>2. PC software via NFC or USB Type-C port</li> </ol>	
<b>Physical Characteristics</b>		
Power Supply	4 × 2700 mAh ER14505 Li-SOCl <sub>2</sub> battery	5V/1A by Type-C Port
Operating Temperature	-20°C - 50°C (E-Ink Screen: 0°C - 40°C)	
Relative Humidity	10% - 90% (non-condensing)	
Ingress Protection	IP30	
Dimension	100.8 × 114 × 22 mm (3.97 × 4.49 × 0.87 in)	
Installation	Wall Mounting	

1. This function is valid in the measurement of either HCHO or O<sub>3</sub>.
2. O<sub>3</sub> electrochemical sensor working life is 2 years.